

# IVR 800 NEW AVANT FLOOR

Collettore di mandata con misuratori di portata, valvola sfogo aria e rubinetto di carico/scarico acqua;  
collettore di ritorno con valvole manuali, valvola sfogo aria e rubinetto di carico/scarico acqua.

Inlet manifold with flow meter, air vent and draining valve;  
return manifold with manual valves, air vent and draining valve.

Vorlaufverteiler mit Durchflussmessern, Entlüftungsventil und Füll - und Entleerungshahn;  
Rücklaufverteiler mit Regulierventilen, Handrädern, Entlüftungsventil und Füll - Entleerungshahn

Collecteur d'alimentation avec débitmètres des circuits, vanne de purge d'air et robinets de remplissage/devidange;  
collecteur de retour avec vannes manuelles, vanne de purge d'air et robinets de remplissage/devidange.

Входной коллектор с расходомерами, воздухоотводчиком и дренажным клапаном;  
Обратный коллектор с ручными регулирующими клапанами, воздухоотводчиком и дренажным клапаном.




Collettore in acciaio inox AISI 304 1" - 1"1/4, connessioni 3/4" EK interasse 50 mm, zanche di fissaggio antivibrazione, etichette e istruzioni.

AISI 304 stainless steel manifold 1" - 1"1/4, 3/4" Eurocone connections centre hole distance 50 mm, mounting brackets which minimise noise and vibration, stickers and assembly instruction.

Verteiler aus rostfreiem Edelstahl AISI 304 mit 1" - 1"1/4, 3/4" anschlüssen Eurokonus abstand 50 mm, schwingungsdämpfenden Befestigungsklammern, etiketten und anweisungen.


Collecteur en acier inox AISI 304 1" - 1"1/4, fixations 3/4" EK entraxes 50 mm, plaques d'ancrage antivibration, étiquettes et instructions.

Коллектор из нержавеющей стали AISI 304, размеры 1" - 1"1/4, 3/4" соединения Евроконус межосевое расстояние 50 мм, крепления с защитой от вибрации, инструкция по сборке.




#### Dati tecnici - Technical data


Pressione massima di esercizio  
Max. working pressure 10 bar



N	DENOMINAZIONE PART NAME	MATERIALE MATERIAL	TRATTAMENTO TREATMENT
1	Zanca Acciaio Mounting brackets	Acciaio Steel	Zincata Zinc plated
2	Valvola manuale Manual valve		
3	Misuratore di portata Flow setting valve		
4	Collettore con misuratori di portata Manifold with flow setting valves	Acciaio inox AISI 304 Stainless steel AISI 304	
5	Collettore con valvole Manifold with valves	Acciaio inox AISI 304 Stainless steel AISI 304	
6	Rubinetto di carico-scarico Draining valve	Ottone - Brass CW 617N - UNI EN 2165/98	Nichelato Nikel plated
7	Sfogo aria Air-vent	Ottone - Brass CW 617N - UNI EN 2165/98	Nichelato Nikel plated



Code	Tipe	F	L	B	C	E
180022502	2 vie	G 1"	179	44	73.5	27
180022503	3 vie	G 1"	229	44	73.5	27
180022504	4 vie	G 1"	279	44	73.5	27
180022505	5 vie	G 1"	329	44	73.5	27
180022506	6 vie	G 1"	379	44	73.5	27
180022507	7 vie	G 1"	429	44	73.5	27
180022508	8 vie	G 1"	479	44	73.5	27
180022509	9 vie	G 1"	529	44	73.5	27
180022510	10 vie	G 1"	579	44	73.5	27
180022511	11 vie	G 1"	629	44	73.5	27
180022512	12 vie	G 1"	679	44	73.5	27
180032506	6 vie	G 1"1/4	379	46.5	79.5	29.5
180032507	7 vie	G 1"1/4	429	46.5	79.5	29.5
180032508	8 vie	G 1"1/4	479	46.5	79.5	29.5
180032509	9 vie	G 1"1/4	529	46.5	79.5	29.5
180032510	10 vie	G 1"1/4	579	46.5	79.5	29.5
180032511	11 vie	G 1"1/4	629	46.5	79.5	29.5
180032512	12 vie	G 1"1/4	679	46.5	79.5	29.5



KVs 1.1 m<sup>3</sup>/h